

MAKROLAM®

2R 1650

Product Overview

The Makrolam 2R is a wide format pressure sensitive laminator. With two opening rollers, it allows processes such as block mounting, lamination of thick items with simultaneous double sided lamination of items. Ideal for applying pressure sensitive films and double sided adhesives to inkjet media as used widely in the signage industry. Perfectly suited to laminating cardboard, foamcore and rigid substrates.

Reliability and Servicing

Built sturdily, with reliable components designed to withstand industrial levels of usage, and low maintenance requirements, the Makrolam 2R will provide quality finishing of a wide range of materials. All components are easily replaceable in the unlikely event of malfunction or damage. Built by a leading manufacturer with 20 years experience in the field, the Makrolam 2R will provide many years of reliable service.

Features

Lamination of items up to 20mm in thickness.

Two 85mm (3.3") diameter Silicone rubber rollers, for the highest quality finish.

Powerful variable speed reversible motor.

No compressor is required for opening rollers.

Upper and lower rewind mandrels for simultaneous double sided lamination.

Meets and exceeds European design standards.

Stable mobile stand, all steel construction with locking castors.

Unwind bracket for long items

Safety footswitch for hands free use.

Optional heat assist roller



Australian designed & made

| Specifications | |
|----------------|---|
| Voltage | 110 or 230 VAC 5 amp |
| Boxed Size | 224 x 72 x 70 cm 88" x 28" x 27" |
| Weight | 250 kg / 670 lb |
| Speed | 0-5 metres per minute 0-17 feet per minute |
| Max. Thickness | 15 mm / .6" |

EMSeal PTY LTD

Australian Manufacture of quality Laminating Machinery

6 Azalea Street
Vermont, Vic 3133
AUSTRALIA



Ph : +61 3 9874 6155
Fax: +61 3 9874 8528
sales@emseal.com.au

www.emseal.com.au
Copyright © 2005 Emseal Pty Ltd